S20 Long Lifter



In addition to the high strength design, the overall length is 26mm and the outer diameter is slightly thicker than the OEM value to reduce the play of the lifter. This allows the camshaft profile to be transmitted to the valves without loss, reducing tappet noise and restoring the original engine performance.

Carburized + Tufftride Inner surface: Shot Outer surface:

Polished finish

HRC45-55 ÿ32.480-32.490 (slightly thick) Long type (total length 26mm) 2-3/100 (design target value) Body ¥132,000 /24 pcs

S20 ENGINE PARTS

S20 reinforced valve set



High-performance valves were created based on metal materials that are resistant to heat and

wear. The valves, which have passed strict inspection standards including "forging + precision machining + heat treatment + quality control," demonstrate their potential and prove their high quality even under harsh operating conditions.

> Unit: ÿ60,000 /SET Unit: ÿ2,500 / Single item

length: IN 106.9mm EX 106.6mm (K4 standard size) *This valve is designed for K4. When using with K3, please use the valve lifter and valve cotter for K4

Tufftride •Surface hardness: together

S20 reinforced valve guide



guides are achieved by using two different materials according to the characteristic of the IN and EX, and by precision machining of the inner and outer diameters. This minimizes the clearance with the valve, improving the accuracy of the valve movement and enabling higher rotation.

Material: IN Aluminum bronze EX Phosphor bronze

Outer diameter STD Body ¥48 000 Outer diameter

0.03OS Body ¥48,000 *Set price

*Please use FJ20 valve oil seal and valve spring stepped seat together. Valve guides are sold individually. Please check the guide hole diameter of the cylinder head before ordering.

S20 Reinforced seat ring (sintered alloy)



ÿOuter diameter Inner diameter Height IN 34.4 28.0 8.5 EX 32.8 26.3 9.2

seat ring is made

of sintered alloy, which has excellent wear and heat resistance, and stabilizes the contact surface of the valve seat from city driving to sports driving.

> Unit ¥48 000 /SET Unit ¥2 000 / Single item *External diameter

FJ20 Repurposed valve oil seal



This is a valve oil seal for the FJ20 that is required when using the KAMEARI reinforced valve guide with the S20.

Unlike the genuine O-ring type, it has high sealing performance and prevents oil

ÿ8,880 Unit price: Set price: ÿ370

nend the KAMEARI reinforced valve guide compatible with the FJ20 valve oil seal.

enuine valve guides, chamfer the outer periphery of the upper end face of the valve guide

S20 K4 Reinforced Valve Cotter



It prevents variations in spring set length caused by over-revving or surging, ing you to maintain the best condition for a long period of time.

Unit price: ÿ19,200

S20 valve spring stepped seat & washer



S20 Valve Spring Stepped Seat KAMEARI This

stepped seat is essential when using reinforced valve guides. It fits perfectly with

double spring and stabilizes the valve spring.

Material: Machined Chromoly 1 set Unit price: ÿ24,000

S20 Standard valve spring set



The metal fatigue of valve springs that have been in use for about 50 years since their manufacture is immeasurable. The valves have become less tightly attached due to the amount of wear that has occurred from the initial load setting, and at the same time, engine output has dropped significantly. This product is a high-performance valve spring developed with the latest technology to restore the original performance of the S20 engine.

Price: ¥60,000/SET

S20 Valve spring washer seat cutting can increase

the protrusion or reduce the load due to sagging of the valve spring by placing a washer under the stepped seat

•Thickness 0.5mm body ÿ350/1 piece•Thickness 1.0mm body ÿ350/1 piece

S20 Reinforced Valve Cap



SCM435 (chrome molybd

HCR45-49 Quenched and

ich meitisch Wedliff mahapape as genuine Same shape as genuine

Price: ¥1,500

A=1.25 A=1.30 A=1.35 A=1.40 A=1.45 A=1.50	A=1.55 A=1.60 A=1.65 A=1.70 A=1.75 A=1.80	A=1.85 A=1.90 A=1.95 A=2.00 A=2.05 A=2.10	A=2.15 A=2.20 A=2.25 A=2.30 A=2.35 A=2.40	A=2.45 A=2.50 A=2.55 A=2.60 A=2.65
A=1.50	A=1.80	A=2.10	A=2.40	



S20 Outer Clearance Cap



This outer cap is used when the thickness of commercially available valve caps is

convenient part that allows you to adjust the clearance by simply placing it on the genuine cap (Kameari valve cap) when using a high cam that has processed by genuine processing, or when using a K4 lifter on a K3 head.

•Thickness (1mm/2mm/3mm)

Price /1 piece Unit price: ÿ1,700



A dimension (tolerance +0.03 -0) Aÿ1.0 Aÿ2.0 Aÿ3.0